



BYDGOSKIE ZAKŁADY SKLEJEK

**SKLEJKA
MULTI SA**

85-752 Bydgoszcz, ul. Fordońska 154
tel. 0-52 342-50-61, fax 0-52 342-06-73

DATA SHEET

Decorative plywood

A plywood composed of glued with phenol-formaldehyde resin or other of similar properties, plies of wood (outer and middle veneers), whereat the directions of fibre of adjacent plies are staggered by 90°. Face veneers (outer veneers) are made of birch, alder or beech. The plywood surface is covered with a decorative foil: one color or wood-veneered or veneered with natural veneer.

Humidity: 10±5% (acc. to EN 322), **density:** do 800 kg/m³ (acc. to EN 323)

Standard sizes:

2500×1250 mm
2440×1220 mm
2130×1220 mm
1530×1530 mm

or acc. to arrangements with the customer.

- length and widths tolerance: ± 3,5 mm (acc. EN 315),
- edge tolerance: ±1,0 mm/m lengths of the side (acc. EN 315).

Thickness range: 4-50 mm

Possibilities of additional processing and finishes

Cutting to smaller sizes , straight and profiled finishing of the edges, drilling, milling of grooves, slots, rabbets - in CNC centres.

Application

Decorative plywood except the high aesthetic properties have high technical properties. It is used inter alia in furniture, interior fittings as part of the walls and ceilings, for furniture production, in transport, furniture production in shipbuilding and boatbuilding and manufacturing various kinds of woodworking and decorative packaging.

Updated 18.08.2014